

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designer registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、域名权、其他知识产权外，本公司保留对涉及发明、实用新型、外观设计、软件著作权、集成电路布图设计专有权、域名权、其他知识产权的所有权利。

FOR-1755 Rev.1.7

2







3

4

5

6

PCB LAYOUT



未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~500	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

UL 标准/UL Standard:

额定电压/电流/Rated Voltage(V)/Current(A)

B

300/20

C

/

D

300/10

IEC 标准/IEC Standard:

过压类别/Overvoltage Category/污染等级/Pollution Degree

III/3

III/2

II/2

额定电压/电流/Rated Voltage(V)/Current(A)

/

250/18

/

工频耐压/Withstanding Voltage(V/min)

/

AC2000

/

螺丝扭矩/Torque Tightening(N·m/Lb.in)

M3, 0.5/4.5

线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)

30~12 / 1.0~2.5

间距/Pitch(mm)/线数范围/Poles

5.0/N=02~24P

剥线长度/Stripping length(mm)

6~7

使用温度范围/Operating temperature(°C)

-40~+105

符合RoHS环保要求/Conform to RoHS

Yes

A

B

C

D

1

2

3

4

5

6