



REV	CONTENT	CHK	DATE
V0.0	CONTENT	MYZ	21.07.03




PCB LAYOUT



SECTION A-A


Electrical :

- | | | |
|--|---------------|------|
| | UL | IEC |
| 1.Rated Voltage : | 300V | 320V |
| 2.Rated Current : | 15A | 20A |
| 3.Withstanding Voltage : | AC1600V/1Min. | |
| 4.Operating Temperature : | -40°C~+105°C | |
| 5. RoHS Compliance | | |
| 6.Safety Approval : | | |
| 7."★" is the key quality control point | | |



2EGTRM - 5.08 - XXP - X X - 00TH

- | | | | | | |
|-------------------|---------|---------------|------------------------------------|--|---|
| ① | ② | ③ | ④ | ⑤ | ⑥ |
| ① Series NO. | ② Pitch | ③ Poles | ④ 1 Single Pitch
2 Double Pitch | ⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White | ⑥ Customer Request: 00TH--
High temperature material |
| 02 02Contacts | | 03 03Contacts | | | |
| ... 24 24Contacts | | | | | |



A	Total Pitch Tolerances									Nominal dimension range									$\perp$		$\equiv$		---		$//$	
	in mm									in mm																
	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10	all	over 0	over 100	over 150		
	to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10		to 100	to 150	to 150		
	±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		

3	NUT	XX	2	COPPER ALLOY	/
2	PIN	XX	P	COPPER ALLOY	Tin Plated
1	HOUSING	XX	1	high temperature material	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	MYZ	DATE	21.07.03	SIZE	A4 UNITS mm SHEET/OF 1/1
CHK.		DATE		SCALE	1:1
APP.		DATE		NAME	2EGTRM-5.08-XXP-XX-00TH
			DWGNO.	XXXX	

Golten 宁波冠泰电子有限公司
NINGBO GOLTEN ELECTRONICS CO., LTD.