

# 0.56" (8888) GREEN

☆PART: KEM-5461AG

☆ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

| ITEM   | SYMBOL          | RATING  | UNIT |
|--|-----------------|---------|------|
| Power Dissipation Per Segment  | Pd              | 90      | mW   |
| Peak Forward Current Per Segment<br>(1/10Duty Cycle,0.1ms Pulse Width) | Ifp             | 90      | mA   |
| Continuous Forward Current Per Segment                                 | If              | 25      | mA   |
| Reverse Voltage Per Segment  | Vr              | 5       | V    |
| Reverse Current Per Segment  | Ir              | 20      | uA   |
| Operating Temperature Range  | Ta              | -35~+85 | °C   |
| Storage Temperature Range  | Tstg            | -35~+85 | °C   |
| Lead Solder Temperature  | 260°C for 3 sec |         |      |

☆ELECTRICAL-OPTICAL CHARACTERISTICS (Ta=25°C)

| Parameter                              | Symbol           | Condition | Min   | Typ | Max | Unit |
|--|------------------|-----------|-------|-----|-----|------|
| Forward Voltage Per Segment            | Vf               | If=20mA   |       | 2.0 | 2.3 | V    |
| Peak Emission Wavelength               | $\lambda_p$      | If=20mA   |       | 572 | 574 | nm   |
| Spectral Lin Half-Width                | $\Delta \lambda$ | If=20mA   |       | 30  |     | nm   |
| Average Luminous Intensity Per Segment | Iv               | If=20mA   | 16    | 18  | 21  | mcd  |
| Segment-to-Segment Luminous            | Iv-M             | If=20mA   | 1.5:1 |     |     |      |

☆Notes:

1. All dimensions are in millimeters(inches).
2. Tolerance is  $\pm 0.25\text{mm}(0.01\text{'})$  unless otherwise specified.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

# 0.56" (8888) RED

☆PART: KEM-5461AS

☆ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

| ITEM   | SYMBOL          | RATING  | UNIT |
|--|-----------------|---------|------|
| Power Dissipation Per Segment  | Pd              | 75      | mW   |
| Peak Forward Current Per Segment<br>(1/10Duty Cycle,0.1ms Pulse Width) | Ifp             | 80      | mA   |
| Continuous Forward Current Per Segment                                 | If              | 25      | mA   |
| Reverse Voltage Per Segment  | Vr              | 5       | V    |
| Reverse Current Per Segment  | Ir              | 20      | uA   |
| Operating Temperature Range  | Ta              | -35~+85 | °C   |
| Storage Temperature Range  | Tstg            | -35~+85 | °C   |
| Lead Solder Temperature  | 260°C for 3 sec |         |      |

☆ELECTRICAL-OPTICAL CHARACTERISTICS (Ta=25°C)

| Parameter                              | Symbol           | Condition | Min   | Typ | Max | Unit |
|--|------------------|-----------|-------|-----|-----|------|
| Forward Voltage Per Segment            | Vf               | If=20mA   |       | 1.7 | 2.0 | V    |
| Peak Emission Wavelength               | $\lambda_p$      | If=20mA   |       | 642 | 645 | nm   |
| Spectral Lin Half-Width                | $\Delta \lambda$ | If=20mA   |       | 20  |     | nm   |
| Average Luminous Intensity Per Segment | Iv               | If=20mA   | 20    | 22  | 25  | mcd  |
| Segment-to-Segment Luminous            | Iv-M             | If=20mA   | 1.5:1 |     |     |      |

☆Notes:

5. All dimensions are in millimeters(inches).
6. Tolerance is  $\pm 0.25\text{mm}(0.01\text{'})$  unless otherwise specified.
7. Lead spacing is measured where the leads emerge from the package.
8. Specifications are subject to change without notice.