

PCB 继电器

TRC2

- Creepage distance:10mm;
- Au-clad contact available
- Transparent sealed available
- Class B/F available
- Conform to RoHS,ELV directive



■ ORDERING CODE 订购代码

TRC2	D	—	12VDC	—	S	—	Z
1	2		3		4		5
1. Relay Model 继电器型号					4. S: Sealed 密封		
2. Coil Power 线圈功率 D=0.4W L=0.25W					5. 触点转换形式 Z: Form C H: Form A		
3. Coil Nominal Voltage 线圈额定电压 5,6,9,12,18,24,48,60VDC							

■ COIL DATA 线圈参数 (at 20℃)

Nominal Voltage额定电压(VDC)	5	6	9	12	18	24	48	60	0.4W
Coil Resistance线圈阻值($\Omega \pm 10\%$)	62	90	202	360	810	1440	5760	7500	
Rated Current额定电流(mA)	80	66.7	44.6	33.3	22.2	16.7	8.3	8	
Max Operate Voltage 最大吸合电压(VDC)	3.5	4.2	6.3	8.4	12.6	16.8	33.6	42	
Min Release Voltage最小释放电压(VDC)	0.5	0.6	0.9	1.2	1.8	2.4	4.8	6.0	
Max Voltage 最大电压	23℃时额定电压的130%								

■ CONTACT DATA 触点参数

Contact Form触点形式	H/Z
Contact Material触点材料	Silver Alloy
Load负载	Resistive load($\cos \phi=1$)
Contact Ratings触点负载	16A 250VAC TV-5A@ 125VAC
Minimum load 最小负载	100mA 5VDC
Max Switching Voltage最大转换电压	440VAC/125VDC
Max Switching Current最大转换电流	16A
Max Switching Power 最大转换功率	4000VA
Contact Resistance接触电阻	100m Ω Max at 6VDC 1A
Life Expectancy寿命	Electrical 电气寿命: 100,000 Operations(at20Operations/minute)
	Mechanical机械寿命: 10,000,000 Operations(at300Operations/minute)


■ CHARACTERISTICS DATA 性能参数

Insulation Resistance绝缘阻值	100M Ω Min at 500VDC
Dielectric Strength Between Open Contacts触点间耐压	1000VAC(for one minute)
Between Contacts and coil触点与线圈间耐压	5000VAC(for one minute)
Operate Time吸合时间	15ms
Release Time释放时间	8ms
Temperature Range环境温度	-40℃to+85℃
Shock Resistance冲击	Operating Extremes动作极限: 10G
	Damage Limits破坏极限: 100G
Vibration Resistance振动	10-55Hz, 1.5mm
Max. switching frequency最大转换频率	Mechanical:18,000operations/hr
	Electrical:1,200operations/hr
Humidity湿度	40-85%
Weight重量	Approx 14g
Safety Standard安全标准	UL cUL


■ APPROVED STANDARDS 安全标准

Model(型号)	Coiling rating (线圈电压)	Safety Standard (安全标准)	Contact rating (触点负载)
TRC2	5 to 60VDC	UL/cUL	16A 250VAC TV-5A@ 120VAC



■ ENGINEERING DATA 设计参数





■ OVERALL AND MOUNTING DIMENSIONS 安装图



安装图



接线图



REMARK (备注):

- 1、产品部分外形尺寸中未注尺寸公差：当外形尺寸 $\leq 1\text{mm}$ 时，公差为 $\pm 0.2\text{mm}$ ；当外形尺寸在 $1\sim 5\text{mm}$ 时，公差为 $\pm 0.3\text{mm}$ ；当外形尺寸 $> 5\text{mm}$ 时，公差为 $\pm 0.4\text{mm}$ 。
- 2、安装孔尺寸中未注尺寸公差均为 $\pm 0.1\text{mm}$ 。

声明:

本产品规格书仅供客户使用时参考，如有更改，恕不另行通知。