

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

1. Rated voltage/current : 300V / 10A
2. Torque value : M2.5 , 3.54Lb.in
3. Wire range : 30~16AWG


1. Rated voltage/current : 250V / 12A
2. Torque value : M2.5 , 0.4N·m
3. Wire range : 0.2~1.5mm²

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 5.0mm, Poles : N=2~12P
- 3.Stripping length : 5~6mm
- 4.Withstanding voltage : AC2000V/1Min
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned tolerances:

Pitch range in mm			Nominal dimension range in mm				
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±2.00

DG332W - 5.0 - XXP - 1Y - 00A (H)

DG332W - 5.0 - XXP - 1Y - 00A (H)
 (Series No.) (Pitch) (Poles) (Single Pitch) (Color)
 1.(Grey)
 2.(Blue)
 3.(Black)
 4.(Green)
 5.(Orange)
 6.(Red)
 7.(Transparent)
 8.(Yellow)
 9.(White)



DETACHED LISTS	PART NO.: /	 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
	APPD: /	NAME: DG332W-5.0-XXP-1Y-00A(H)			
	CHKD: /				
	DRFT: /	TITLE: CUSTOMER DRAWING		REV	D0
	 THIRD ANGLE PROJECTION	DRAWING NO.: /		SHEET	1/1
	 DO NOT SCALE DRAWING		SCALE	1:1	